

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification<sup>6</sup> : H04R 1/10, H04M 1/05</p>	<p>A1</p>	<p>(11) International Publication Number: <b>WO 99/60816</b> (43) International Publication Date: 25 November 1999 (25.11.99)</p>
<p>(21) International Application Number: PCT/AU99/00380 (22) International Filing Date: 20 May 1999 (20.05.99) (30) Priority Data: 67977/98 20 May 1998 (20.05.98) AU (71)(72) Applicant and Inventor: LOGAN, Ty [AU/AU]; Unit 16, 1-5 Harwood Street, Pyrmont, NSW 2009 (AU). (74) Agent: CARTER SMITH &amp; BEADLE; Level 10, 189 Kent Street, Sydney, NSW 2000 (AU).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p> <p><b>Best Available Copy</b></p>

(54) Title: HEAD WORN ENTERTAINMENT AND/OR COMMUNICATION DEVICE



(57) Abstract

A head worn entertainment and communication device (10, 110) including at least a first ear assembly (11, 112) which further includes a transducer (19, 119) in communication with a radio receiver housed within an equipment module (27, 127). In particular forms the ear assembly includes a lower limb (20, 120) and an upper limb (22, 122) defining an ear containing space (23, 123) therebetween. In other particular forms a first ear assembly (11) is interconnected with a second ear assembly (12) by means of an interconnect device (13).

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

## HEAD WORN ENTERTAINMENT AND/OR COMMUNICATION DEVICE

The present invention relates to a head worn entertainment and communication device and, more particularly, to such a device adapted to be worn whilst engaging in swimming activities such as doing laps of a pool and the like.

5

### Background

There are occasions when it would be desirable to be able to listen to the radio or other form of audio communication whilst engaged in swimming activities. In the case of competition swimmers they often spend long hours doing laps of pools and it would be advantageous, for example, to listen to the radio to help while the time away.

10

It is known to provide a radio module which can be strapped to the body or contained in clothing and which is connected by a cable to an ear piece. These forms of body worn communication devices are not suitable for use in the water and, even if waterproofed, would tend not to stay in place during vigorous swimming activity such as doing laps of a pool.

15

It is an object of the present invention to provide a swimmers head worn entertainment and communication device which addresses one or more of the abovementioned problems and needs.

### 20 Brief Description of Invention

In a first aspect the present invention provides a head worn entertainment and/or communication device comprising a first ear assembly, a transducer for converting an electrical signal to an auditory signal, a radio receiver in communication with the transducer and wherein the first ear assembly comprises an upper limb and a lower limb for fitment to the ear.

25

Preferably, the upper limb and the lower limb of the first ear assembly define an ear containing space.

In use of present invention, the first ear assembly is positioned relative to the ear such that the upper limb and lower limb extend at least partly, and preferably substantially, around the ear to thereby hold the first ear assembly in place. The

30

- 2 -

transducer is preferably carried by, fixed to or formed with the first ear assembly such that the transducer is positioned within or in close proximity to the ear when the first ear assembly is fitted to the ear. Even more preferably, the transducer is positioned within an ear plug that, in use, fits inside the ear canal of the user. The transducer is most preferably supported by the first ear assembly, especially by one of the upper or lower limbs, most preferably the lower limb. The transducer and receiver may be formed as an integrated unit. This would preferably be mounted on the first ear assembly.

It is preferred that the device of the present invention further comprises a first equipment module. The first equipment module may be positioned on or carried by the first ear assembly or it may be located away from the first ear assembly. The first equipment module may contain the radio receiver therein.

In another embodiment of the present invention, the first ear assembly is connected to an interconnect device, which interconnect device is adapted to extend at least partly around the head of a user of the device. The interconnect device may comprise a first support means and a second support means connected to each other by an adjustable length means, said first and second support means being generally opposed to each other. The adjustable length means may comprise an adjustable length concertina tube. Alternatively, the adjustable length means may comprise a deformable member. The length of the deformable member be adjusted by deforming the deformable member.

The first support means preferably comprises a first semi rigid support. In this regard, the semi rigid support may be deformable or flexible to allow close fit to the head of a user of the device. The first support means may comprise a deformable or flexible plastics material, a wire, a deformable metal member, or the like.

Similarly, the second support means is preferably a second semi rigid support. The second support means may be deformable or flexible to allow close fit to the head of a user. The second support means preferably comprises a deformable or flexible plastics material, a wire, a deformable or flexible metal material or the like.

The second support means, in one embodiment of the invention, terminates in a stub. In this embodiment, the device of the present invention is fitted to the head of a user by placing the first ear assembly around or on one ear of the user and positioning

- 3 -

the second support means such that it extends at least partly along the other side of the head of the user. Adjustment of the first and/or second support means and/or the adjustable length means, thereby assists in holding the device securely to the head of the user.

5 In a further embodiment of the present invention, the second support means has a second ear assembly connected thereto. The second ear assembly may comprise an upper limb and a lower limb for fitment to the other ear of the user. The upper and lower limbs preferably define an ear containing space. The second ear assembly may also include a transducer for converting an electrical to an auditory signal. In this  
10 regard, the transducer of the second ear means is preferably in communication with the radio receiver.

The transducer of the second ear assembly is preferably positioned at such that, in use, it is positioned within or in close proximity to the ear of the user. More preferably, the transducer of the second ear assembly is positioned within an earplug  
15 that, in use, fits inside the ear canal of the user.

The upper limb and/or the lower limb of the first and/or second ear assemblies may of adjustable shape to enable the upper and/or lower limbs to more closely conform to the ear of the user. The upper and/or lower limbs may include at least one portion of adjustable shape, such as a concertina tube portion.

20 The first equipment module is preferably positioned on or formed on the first support means. Cabling may extend from the first equipment module to the first ear assembly and, in embodiments that include a second ear assembly as well, such that electrical signals from the radio receiver can be transmitted to the respective transducers in the first and second ear assemblies. The cabling preferably passes  
25 through the inside of the device such that there is no external cabling. The cabling most preferably passes through the interconnect device to the first ear assembly and the second ear assembly, where provided.

The apparatus of the present invention preferably further comprises a second equipment module. The second equipment module is preferably carried by or formed  
30 with the second support means. Preferably, the second equipment module is generally opposed to the first equipment module.

- 4 -

The second equipment module preferably contains the battery or batteries for use in the device. Power cable(s) may extend from the second equipment module to the first equipment module. Preferably, the power cable(s) pass through the inside of the device, most preferably through the interconnect device.

5 In order to enable the device to be used for water sports or aquatic purposes, it is preferred that the device is essentially waterproof. In this regard, the first and second equipment modules should be waterproof. The second module may have a removable cover to allow the batteries to be changed. The removable cover is preferably fitted with a water tight seal or gasket, as will be known to those skilled in the particular art.

10 The transducer or transducers may be speakers. Alternatively, they may be bone conduction hearing devices, in which case they are preferably located such that, in use, they are in contact with bone behind the ear.

The device of the present invention is preferably used as part of a communication and/or entertainment system which also comprises a radio transmitter  
15 for transmitting radio signals to the radio receiver. Preferably, the radio transmitter is a low powered transmitter and it may have a maximum transmission of up to 1 km, or even less. The radio transmitter may include a microphone to enable verbal communication to pass from the person using the microphone to the person wearing the device. This is particularly useful in cases where swimming coaches wish to give  
20 instructions to swimmers training in the water. Alternatively, the radio transmitter may re-transmit a radio signal from a local radio station or it may receive an input signal from a tape player or CD player and transmit that signal to the radio receiver of the device. This allows the user of the device to choose his or her own music. The radio transmitter may have an input jack to facilitate this function.

## 25 **Brief Description of Drawings**

Embodiments of the invention will now be described with reference to the accompanying drawings wherein:

Fig. 1 is a perspective view of a head worn entertainment and communication device according to a first embodiment of the invention,

30 Fig. 2 is a side view of the device of Fig. 1 in place on a swimmer's head,

- 5 -

Fig. 3 is a diagrammatic representation of a swimmers head worn entertainment and communication device according to a second embodiment of the invention.

Fig. 4 is a perspective view of a head worn entertainment and communication device according to a third embodiment of the invention.

5 Fig. 5 is a perspective view of a head worn entertainment and communication device according to a fourth embodiment of the invention.

### Detailed Description of Preferred Embodiments

With reference to Fig. 1 there is shown a swimmers head worn entertainment and communication device 10 comprising, in this instance, a first ear assembly 11 connected in opposed relationship to a second ear assembly 12 by means of interconnect device 13.

The interconnect device 13 comprises a first semi-rigid support 14 connected in opposed relationship to a second semi-rigid support 15 by an adjustable length concertina unit 16 (shown in detail in the insert of Fig. 1).

15 The semi-rigid supports 13, 15 can take the form of elongate rods made from a plastics material. The adjustable length concertina unit 16 can take the form of a tubular plastics material having hingedly interconnected ferrules adapted to collapse one against the other about hinges 18.

In this instance first ear assembly 11 is constructed in the same manner as 20 second ear assembly 12 and comprises transducer 19 supported on lower limb 20 from a free end 21 of the respective semi-rigid supports 14, 15.

Each ear assembly 11, 12 further includes an upper limb 22 integrally attached to free end 21 and opposed to lower limb 20 so as to define an ear containing space 23 therebetween.

25 Both lower limb 20 and upper limb 22 are curved so as to follow at least part of the contour of a human ear as best seen in Fig. 2. They are sufficiently curved that they substantially encircle the ear save for an entry region 24 which presents a sufficient aperture to allow the ear assemblies 11, 12 to be engaged about an ear 25 by a sliding approach of aperture 24 approaching from the rear of the ear.

30 In this instance the limbs 20, 22 are made from the same plastics material as the semi-rigid supports 14, 15 and are integrally moulded therewith.

- 6 -

The upper and/or lower limb can include an adjustable length concertina unit. In this instance the upper limb 22 is formed of two segments joined by concertina unit 26 thereby allowing adjustment for the ear containing space 23 according to the requirements of the user.

5           The entertainment and communication device 10 further includes an equipment module 27 threaded onto or formed with second semi-rigid support 15 and a similar module 29 threaded onto or formed with first semi-rigid support 14 as shown.

          In this instance the equipment module 27 contains an AM and FM radio receiver whose audio out jack is connected by cable 28 to transducer 19, which  
10   transducer is shaped to fit snugly into the entry to the auditory canal of a user as best seen in Fig. 2. Equipment module 27 may include an on/off switch and a volume control (not shown).

          In this instance the semi-rigid supports 14, 15, the lower limbs 20 and the adjustable length concertina unit 16 are hollow and permit cable 28 to be threaded  
15   therethrough.

          The rigidity of the semi-rigid supports 14, 15 and the concertina unit 16 is selected so that when the ear assemblies 11, 12 are mounted about the ears of a user in opposed relationship they apply a gentle pressure to the head of the user so as to assist retention in place of the entertainment and communication device.

20           In this instance the second equipment module 29 can contain batteries connected by a cable (not shown) to the radio within module 27.

          In use a user turns the radio unit on and selects a radio station and listening volume satisfactory for that user. The user then places the entertainment and communication device about their head as above described and so as to achieve the  
25   orientation illustrated in Fig. 2.

          The user may then swim laps of a pool of the like whilst listening to the radio, the arrangement being such that relatively little drag is added and, such drag that there is, does not dislodge the entertainment and communication device from the head of the wearer.

30           Turning to Fig. 3. a second embodiment of the swimmers head worn entertainment and communication device 30 illustrated comprising, in this instance, the



- 7 -

device 10 of Fig. 1 into which has been installed a radio receiver 31 adapted to be in communication with a local transmitter 32. The transmitter 32 is in communication with a head set 33 having ear braces 34 and microphone 35 and connector cable 36 adapted to allow local radio communication with transmitter 32 which, in turn, is in communication with radio receiver 31. With this arrangement a coach or like person can wear headset 33 and have mounted elsewhere on their person the local transmitter 32 and, with this arrangement communicate with device 10 whilst a swimmer is doing laps in a pool.

Alternatively, the unit can be tuned to the frequency of local transmitter 32 for reception of broadcasts from that unit instead.

The arrangement can be such that normally the swimmer will have their unit 31 tuned to a radio station, a transmission from the headset 33 as and when it occurs.

In an alternative embodiment one of either the first ear assembly 11 or second ear assembly 12 can be omitted, but leaving a sufficient stub end at the free end 21 for the purpose of ensuring that it can provide the necessary reactive pressure against the head of a user, equal and opposite to the pressure being applied to the other side of the head of the user by the remaining ear assembly.

In a further alternative embodiment of the invention interconnect device 13 can comprise only the cabling necessary to provide electrical power and communication between the ear assemblies and the radio or like communications device in the equipment module 27.

With reference to the arrangement shown in Fig. 3 input jack 37 to local transmitter 32 can receive audio input from a walkman, CD player or other source of audio input for subsequent communication to the radio receiver 31 of the swimmers head worn entertainment and communication device 10.

With reference to Fig. 4 a further embodiment of the invention is illustrated wherein free end 21 of semi rigid support 14 in this instance comprises a stub 38 of a dimension sufficient to permit a user to adjust pressure applied to a users head located between the stub 38 and the ear assembly 12.

Fig. 5 illustrates a further embodiment of the invention in this instance comprising a single ear assembly 112 including a transducer 119 in communication with an equipment module 127 housing a radio receiver (not shown). Component parts

- 8 -

are identified by numerals as for earlier embodiments, except that a prefix numeral 1 has been added.

The present invention may be used for a number of on-land and in-water aquatic activities.

- 5        The above describes only some embodiments of the present invention and modifications, obvious to those skilled in the art, can be made thereto without departing from the scope and spirit of the present invention.

- 9 -

~~CLAIMS~~

1. A head worn entertainment and/or communication device comprising a first ear assembly, a transducer for converting an electrical signal to an auditory signal, a radio receiver in communication with the transducer and wherein the first ear assembly comprises an upper limb and a lower limb for fitment to the ear.
2. A device as claimed in claim 1 wherein the upper limb and the lower limb define an ear-containing space.
3. A device as claimed in claim 1 or claim 2 wherein the transducer is carried by or fixed to the first ear assembly such that the transducer is positioned within or in close proximity to the ear when the first ear assembly is fitted to the ear.
4. A device as claimed in any one of the preceding claims further comprising a first equipment module.
5. A device as claimed in claim 4 wherein the radio receiver is contained within the first equipment module.
6. A device as claimed in any one of the preceding claims wherein the first ear assembly is connected to an interconnect device, the interconnect device adapted to extend at least partly around the head of a user of the device.
7. A device as claimed in claim 6 wherein the interconnect device comprises a first support means and a second support means connected by an adjustable length means, said first and second support means being generally opposed to each other.
8. A device as claimed in claim 7 wherein the adjustable length means comprises an adjustable length concertina tube.

- 10 -

9. A device as claimed in any one of claims 6 to 8 wherein the first support means comprises a first semi-rigid support.
- 5 10. A device as claimed in any one claims 6 to 8 wherein the first support means is deformable to allow close fit to the head of the user.
11. A device as claimed in any one of claims 6 to 10 wherein the second support means comprises a second semi-rigid support.
- 10 12. A device as claimed in any one of claims 6 to 10 wherein the second support means is deformable to allow close fit to the head of a user.
13. A device as claimed in any one of claims 6 to 12 wherein the second support means terminates in a stub.
- 15 14. A device as claimed in any of claims 6 to 12 further comprising a second ear assembly connected to the second support means.
15. A device as claimed in claim 14 wherein the second ear assembly comprises an upper limb and a lower limb for fitment to the ear.
- 20 16. A device as claimed in claim 15 wherein the upper limb and the lower limb of the second ear assembly define an ear containing space.
- 25 17. A device as claimed in any one of claims 14 to 16 wherein the second ear assembly is generally opposed to the first ear assembly.
18. A device as claimed in any one of the previous claims further comprising a second equipment module.
- 30 19. A device as claimed in claim 18, when appended to any one of claims 7 to 17, wherein the second equipment module is connected to or formed with the second support means.

- 11 -

20. A device as claimed in claim 18 or claim 19 wherein the second equipment module is adapted to contain one or more batteries.
- 5 21. A device as claimed in any one of the preceding claims wherein the upper limb and/or the lower limb of the first ear assembly is of adjustable shape.
22. A device as claimed in claim 21 wherein the upper limb and/or the lower limb include at least one portion of adjustable shape.
- 10 23. A device as claimed in claim 22 wherein at least one portion of adjustable shape comprises a concertina tube.
24. A device as claimed in any one of claims 15 to 23 wherein the upper limb and/or the lower limb of the second ear assembly is of adjustable shape.
- 15 25. A device as claimed in claim 24 wherein the upper limb and/or the lower limb include at least one portion of adjustable shape.
26. A device as claimed in claim 25 wherein the at least one portion of adjustable shape comprises a concertina tube.
- 20 27. A device as claimed in any one of the preceding claims wherein the transducer is positioned within an ear plug that fits within the ear canal of a user.
- 25 28. A device as claimed in any one of claims 14 to 27 wherein the second ear assembly includes a second transducer for converting an electrical signal to an auditory signal.
- 30 29. A device as claimed in claim 28 wherein the second transducer is positioned within an earplug that fits within the ear canal of a user.
30. A device as claimed in any one of claims 4 to 29 wherein the first equipment module is essentially waterproof.

31. A device as claimed in any one of claims 18 to 30 wherein the second equipment module is essentially water proof.
- 5 32. A device as claimed in one of claims 4 to 31 wherein the first equipment module includes an on/off switch for switching the radio on or off.
- 10 33. A device as claimed in any one of claims 20 to 32 wherein the second equipment module includes a removable cover to enable changing of the one or more batteries.
- 15 34. An entertainment or communication system comprising a device as claimed in any one of the preceding claims and a radio transmitter for transmitting radio signal to the radio receiver.
- 20 35. A system as claimed in claim 34 wherein the radio transmitter has a range of about 200 metres.
- 25 36. A system as claimed in claim 34 or claim 35 wherein the radio transmitter includes a microphone to allow verbal instructions to be passed to the radio receiver.
37. A device as claimed in any one of claims 1 to 33 wherein the device further comprises a volume switch for controlling the volume of the auditory signal.
38. A device as claimed in any one claims 6 to 33 wherein the interconnect device incorporates a cable for the conduction of power and/or electrical signals.




Fig. 1




Fig. 2






Fig. 3




Fig. 4




Fig. 5

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU 99/00380

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>		
Int Cl <sup>6</sup> : H04R 1/10; H04M 1/05		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b>		
Minimum documentation searched (classification system followed by classification symbols) IPC : H04R 5/033, 25/02, 1/10, 5/03; H04B 1/34, 1/03, 1/06; H04M 1/04, 1/05, 1/06		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WPAT : (RADIO OR RECEIVER:) AND (HEAD: OR EAR:) AND (HOOK OR CLIP OR SUPPORT:)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 4893344 (Tragardh, Jan et al) 9 January 1990 whole document whole document	1-4 5-38
X A	WO 96/02119 (Plantronics, Inc.) 25 January 1996 whole document whole document	1-4 5-38
A	GB 2226931 (The Plessey Company plc) 11 July 1990 whole document	1-38
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&amp;" document member of the same patent family</p>		
Date of the actual completion of the international search 2 June 1999		Date of mailing of the international search report 15 JUN 1999
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No.: (02) 6285 3929		Authorized officer  JAMES WILLIAMS Telephone No.: (02) 6283 2599

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU 99/00380

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 4335281 (Scott et al) 15 June 1982 whole document whole document	1-4 5-38

# INTERNATIONAL SEARCH REPORT

## Information on patent family members

International application No.  
PCT/AU 99/00380

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
US	4893344	CA	1295408	DE	3831207	DK	5152/87
		FR	2621769	GB	2210534		
WO	96/02119	AU	29516/95				
US	4335281	CA	1181160	CA	1181161	DE	3120013
		GB	2079099	GB	2138649	JP	57030491

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- ✓ • TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

**THIS PAGE BLANK (USPTO)**